

MOEN® 摩恩

浴室配件

如需安装支持，配件丢失等，请联系MOEN。
(中国) 400-630-8866
www.moen.cn

©2023 Moen Incorporated

注意事项：



MOEN® 摩恩 卫浴产品以精湛的技术制造而成，保证品质优良，美观耐用。
清洁产品时须小心，避免对产品表面造成损害。
请用清水或中性的清洁剂清洁产品表面，然后以柔软的毛巾抹干；

切勿使用含化学成分或腐蚀性的清洁剂、粗糙的布料抹擦。

建议定期清洗产品，以保证其外观光洁明亮。
使用酸性清洁剂清洗附近物品时，有可能损害产品表面，请加倍小心。

安装步骤：

1. 在安装位置打1组 $\varnothing 6$ 深30mm的孔。
2. 将两个膨胀套打进孔中，端面与墙面平齐。
3. 用自攻螺丝将固定座锁紧到安装位置。
4. 整组挂件安装，用十字螺丝刀将底座锁紧。
5. 嵌入装饰盖帽。




ACC2401
双层浴巾架

1

安装步骤：



1. 在安装位置打1组 $\varnothing 6$ 深30mm的孔。
2. 将两个膨胀套打进孔中，端面与墙面平齐。
3. 用自攻螺丝将固定座（注意斜面向下）锁紧到安装位置。
4. 整组挂件安装，用内六角扳手将底座锁紧。



2

安装步骤：


1. 在安装位置打1组 $\varnothing 6$ 深30mm的孔。
2. 将两个膨胀套打进孔中，端面与墙面平齐。
3. 用自攻螺丝将固定座（注意斜面向下）锁紧到安装位置。
4. 整组挂件安装，用内六角扳手将底座锁紧。



ACC2407
单衣钩


3

安装步骤：



ACC2404
毛巾环


选装品参考图示



ACC2409
挂钩6件套


4

安装步骤：





ACC2405
带盖纸巾架

安装步骤：



ACC2406
马桶刷架






ACC2411
单杆组件

5


安装步骤：

1. 在安装位置打1组 $\varnothing 6$ 深30mm的孔。
2. 将两个膨胀套打进孔中，端面与墙面平齐。
3. 用自攻螺丝将底座锁紧到安装位置。
4. 整组挂件安装，用十字螺丝将排衣钩锁紧。
5. 分别装上2个装饰盖，旋紧固定。




ACC2408
四排衣钩

6



建议安装中心距320~520mm


ACC2402
双杆毛巾杆650MM



建议安装中心距220~370mm


ACC2412
双杆毛巾杆500MM

7



建议安装中心距320~605mm

ACC2403
单杆毛巾杆650MM





建议安装中心距220~455mm

ACC2413
单杆毛巾杆500MM


8

安装步骤：

1. 首先依次将两支挂钩放入下层篮子的两边槽内。
2. 将产品放在要安装的墙面位置，靠紧墙面保持两支挂钩垂直后，用铅笔在挂钩的孔。上画好需要打孔的记号。
- 3.按照安装尺寸钻孔 并装入膨胀套
4. 用自攻螺丝垫上螺纹接头，依次穿过下层篮子两边和两边挂钩杆上通孔；将其轻锁固定墙面上。
5. 用自攻螺丝垫上螺纹接头，依次穿过下层篮子两边和两边挂钩杆上通孔；将其轻锁固定墙面上。
6. 将上篮及下篮同步一起锁紧固定。
7. 分别装上4个装饰盖，旋紧固定。





9



ACC2414
双层角篮

安装步骤：

1. 在安装位置打1组 $\varnothing 6$ 深30mm的孔。
2. 将两个膨胀套打进孔中，端面与墙面平齐。
3. 用自攻螺丝将底座锁紧到安装位置。
4. 先将小的螺丝穿过置物平台与纸纸巾杆锁紧。
5. 整组挂件安装，用十字螺丝刀将底座锁紧。





ACC2410
带置物台厕纸架

10

安装步骤：

1. 将产品放在要安装的墙面位置,保持与墙面齐平，然后用铅笔在篮子四个孔上画好需要打孔的记号。
2. 按照安装尺寸钻孔并装入膨胀套。
3. 用自攻螺丝垫上螺纹接头，依次穿过单层篮子两边的四个通孔，将其锁紧固定在墙面上。
4. 分别装上4个装饰盖，旋紧固定。



ACC2415
单层篮

11

产品售后保修条款

摩恩产品是在质量标准及生产工艺下制造的，摩恩承诺为消费者购买的洁具产品提供有期限免费保修及终身维修服务。
浴室配件免费保修期为1年，均自消费者购买日（以摩恩产品分销商开具的发票或收据上载明日期为准）起计。
免费保修范围为产品及产品配件由于材质及工艺原因而造成的故障或损坏。免费保修期内，我们将无偿为您提供维修服务及更换发生故障的产品或产品配件。摩恩的售后服务责任仅限于对故障产品的修理，而不延及您因产品故障而发生的其他损失，法律另有规定的除外。
您需了解：产品外观碰伤、刻划痕迹，以及滥用及不正当保养所导致的故障或损坏，均不属于免费保修范围。即使在免费保修期内，属下列（1）-（5）情况之一的，需酌情收取修理费用：
1. 不能出示相符的保修卡和有效购买凭证情况的，
2. 未按使用说明告知的使用方法和注意事项造成的故障，
3. 自行拆卸、维修、改装所造成的故障和损坏，
4. 由于不可抗力等外部原因引起的故障和损坏，
5. 由于运输、搬运、挤压等造成的损坏。

对于保修期外或不在保修范围内的产品，如需维修，摩恩将酌情收取上门费、人工费及材料费。
本保修条款仅对原始消费者和酒店行业的购买者有效，并不适用于本产品工业，商业，贸易和非酒店行业的使用。
如对本保修条款内容有任何疑问，请拨打400 630 8866 咨询热线，或向当地分销商咨询。

MOEN® 摩恩

合格证
Compliance Certification

产品名称
Product Name
浴室配件
Bathroom Accessories

检验员
Inspector

生产日期
Date of Production

富俊仁德科技(上海)有限公司
中国(上海)自由贸易试验区新杨公路
1800弄1号4幢207室
邮编: 201413

Fortune Brands Innovations (Shanghai) Co., Ltd
Room 207, Building 4, No.1, Lane 1800, Xinyang Highway,
China (Shanghai) Pilot Free Trade Zone

MOEN® 摩恩

Bathroom Accessories

PLEASE CONTACT MOEN FIRST
For Installation Help, Missing or Replacement Parts
(China) 400-630-8866
www.moen.cn

©2023 Moen Incorporated



CAUTIONS:

MOEN® 摩恩 Bathroom products are made with superb technology to ensure high quality, beautiful and durable.
Be careful when cleaning the product to avoid damage to the surface of the product.
Please clean the surface of the product with water or neutral detergent, and then dry it with a soft towel;


Do not use chemical or corrosive cleaners or rough cloths.

It is recommended to clean the product regularly to ensure its appearance is bright and clean.
When using acidic cleaners to clean nearby items, it may damage the surface of the product.
Please be extra careful.

- Installation Guide:
1. Drill a group of $\phi 6$, deep 30mm holes in intended position.
 2. Place plug into holes, makes its end is flush with wall.
 3. Use screw to lock the base to installation position.
 4. Install Assembly, use cross screwdriver to lock the base.
 5. Place two end caps to cover screws, make them tightened.






- Installation Guide:
1. Drill a group of $\phi 6$, deep 30mm holes in intended position.
 2. Place plug into holes, makes its end is flush with wall.
 3. Use screw to lock the base to installation position. Please make the side with slant downside.
 4. Install Assembly, use hex to lock the base.




2

- Installation Guide:
1. Drill a group of $\phi 6$, deep 30mm holes in intended position.
 2. Place plug into holes, make its end is flush with wall.
 3. Use screw to lock the base to installation position.
 4. Install the whole accessory and use hex to lock the base to



ACC2404
Towel Ring


Intended product picture



Note: Commonly use for
towel rack/towel rail/towel
ring ect. in this collection.

ACC2409
Accessory 6 Kits

4




ACC2405
Covered Tissue Holder





ACC2406
Toilet Brush Holder

ACC2403+ACC2411 Please see sub-assembly detail



ACC2413+ACC2411






Sub-assembly detail

Assembly Step:
1. Prior to Assembly, please take out the plastic cap at the end of towel bar.
2. Place screw at mid of connector between towel bar and intended parts, make it locked tightly. See as illustrator.

ACC2411
Sub-assembly Towel Rail


5

- Installation Guide:
1. Drill a group of $\phi 6$, deep 30mm holes in intended position.
 2. Place plug into holes, makes its end is flush with wall.
 3. Use screw to lock the base to installation position.
 4. Install the whole accessory, use Philip screw to lock the Hook.
 5. Place two end caps to cover screws, make them tightened.




ACC2408
Row Hook

6




Recommended center distance 320~520mm
ACC2402
Double Towel Rail 650mm




Recommended center distance 220~370mm
ACC2412
Double Towel Rail 500mm

7



Recommended center distance 320~605mm
ACC2403
Single Towel Rail 650mm





Recommended center distance 220~455mm
ACC2413
Single Towel Rail 500mm

8


Installation Guide:

1. Place two hooks hanged on the lower basket.
2. Place basket against wall, use pencil to mark the intended drilling position.
3. Drill and place plug.
4. Use screw with joint to lock hooks and lower basket together and fix it against wall.
5. Use screw with joint to lock hooks and upper basket together and fix it against wall.
6. Lock upper and lower basket tightly.
7. Place end cap to cover the four screws and make them locked tightly.





ACC2414
Double Shower Basket

9



Installation Guide:

1. Drill a group of $\phi 6$, deep 30mm holes in intended position.
2. Place plug into holes, makes its end is flush with wall.
3. Use screw to lock the base to installation position.
4. Make the small screw through tray and locked with Tissue Holder.
5. Install the whole Assembly, use Philip screw to lock tightly.





ACC2410
Tissue Holder with Tray

10

Installation Guide:

1. Place the product on intended position against wall, and marks the intended position to drill 4 holes.
2. Drill four holes and place plugs.
3. Place four screws through the holes on basket and lock tightly onto wall.
4. Place four end caps to cover the four screws, make them locked tightened.



ACC2415
Shower Basket

11

MOEN LIMITED WARRANTY

We offer limited warranty and lifetime maintenance for Moen products, which are all manufactured with high standards of workmanship.
The period of warranty shall start from the date of purchase of the product (according to the invoice or receipt issued by Moen distributors) and shall cover a period of the following: the warranty period for Bathroom Accessory is 1 year.
This warranty is your coverage against material and workmanship malfunction or defects in Moen products or components. During the warranty period, we offer free maintenance and changing of malfunctioned products or product components. Moen's after sales service liability is limited to the maintenance of faulty items and does not cover your other losses caused by product malfunction, except for otherwise stipulated by law.
Cosmetic damages (scratches, dents, etc.) and malfunction or defects caused by abuse or improper maintenance is not covered by this warranty.
Although the warranty period remains valid, in case of the following conditions (1) - (5), the maintenance cost (material cost and labor cost) shall still be charged as the case may be:
1. Corresponding warranty card and valid invoice cannot be presented;
2. Faults were caused by the noncompliance with the instructions and precautions provided in the user's manual;

3. Damages and faults were caused by self-actuated dismantling, repair and refit;
4. Faults and damages were caused by external factors such as force majeure;
5. Damages were caused by transportation, unloading and extrusion, etc.
This warranty is valid for the original consumers only (including hotel use), and excludes industrial and commercial use of the product (except for hotel use). This card is only responsible for product maintenance rather than any other liabilities.
In the event that the product requires maintenance but exceeds the warranty period, or that the product is not covered by this warranty, labor cost and material cost shall be charged as the case may be.
Please call 400-630-8866 or contact local dealer for any question.

